

This Owner's Manual is provided and hosted by [Appliance Factory Parts](#).



Charbroil 463550505 Owner's Manual

[Shop genuine replacement parts for Charbroil
463550505](#)



[Find Your Charbroil Grill Parts - Select From 3592 Models](#)

----- Manual continues below -----

Parts List - Model 463550505

<u>Key</u>	<u>Qty.</u>	<u>Description</u>	<u>Part #</u>	<u>Key</u>	<u>Qty.</u>	<u>Description</u>	<u>Part#</u>
A	1	Vaporiser Bar.....	4151037	1	1	Hardware Bag, Cart.....	4254079
B	2	Side Shelf.....	4154279	2	2	Hardware Bag, Shelves.....	4254074

1

Parts to assemble:

- 1 Leg Assembly
- 1 Front Panel
- 2 Side Support Braces
- 4 Carriage Bolt, 2"
- 4 Plastic Tie Knob

A. Lay leg assemblies on their sides.
 B. Place front panel on legs.
 C. Place side support braces on legs.
 D. Secure with carriage bolts and tie knobs.

Front Panel
 Leg Assembly
 Side Support Braces

Qty. 4
 Qty. 4

NOTE: To prevent scratching, lay grill or packing material to assemble.

2

Parts to assemble:

- 1 Vapouriser Bar
- 1 Back Support Brace
- 4 Carriage Bolt, 2"
- 4 Plastic Tie Knob

A. Turn assembly inside-down.
 B. Secure back brace and side support braces with carriage bolts and tie knobs.

Back Support Brace
 Side braces on inside of legs.

Qty. 4
 Qty. 4

3

Parts to assemble:

- 1 Tank Support Bracket
- 2 Axle Bolt
- 2 High Pin
- 2 Leg Extender

A. Insert axle bolts through wheels, axle brackets, and inside legs.
 B. Secure with high pins in ends of axle bolts.
 C. Push leg extenders into right legs.

Wheel
 Tank Support Bracket
 Leg Extender

Qty. 2
 Qty. 2

4

Parts to assemble:

- 1 Grill Bottom Assembly
- 4 Carriage Bolt, 1/2"
- 4 Metal Wing Nut
- 2 Control Knob

A. Stand cart upright.
 B. Make sure ignitor wire is connected to ignitor.
 C. Place grill bottom on supports. Control knobs should be on the right side.
 D. Secure with carriage bolts and wing nuts.
 E. Press control knobs onto valves.

Grill Bottom
 Control Knobs
 Control Panel
 Ignitor Wire

Qty. 4
 Qty. 4

5

Parts to assemble:

- 1 Vapouriser Bar
- 1 Cooking Grate

A. Place vapouriser bar onto the two inner support ridges at each end of grill bottom. Bar should rest between the outer support ridges.
 B. Place cooking grate onto grill bottom.

NOTE: Ceramic briquets are not required.

Vapouriser Bar
 Cooking Grate
 Outer Support Ridge

Qty. 1
 Qty. 1

6

Parts to assemble:

- 2 Side Shelf
- 8 Carriage Bolt, 2"
- 8 Plastic Tie Knobs

A. Place shelves onto legs (curved edge inward).
 B. Secure with carriage bolts and tie knobs.

Side Shelf
 Curved Edge

Qty. 8
 Qty. 8

7

Parts to assemble:

- 1 Grill Lid
- 1 Handle
- 1 Machine Screw, 1/2"
- 1 Metal Wing Nut
- 2 High Pin
- 2 High Pin

A. Attach lid to grill bottom with machine screw and metal wing nut.
 B. Attach handle to lid with machine screw and metal wing nut.

Handle
 Grill Lid

Qty. 1
 Qty. 2
 Qty. 1
 Qty. 2

8

Parts to assemble:

- 1 Tank Retainer Wire
- 1 Carriage Bolt, 1/4"
- 1 Plastic Tie Knob

A. Attach retainer wire to left side brace with carriage bolt and tie knob. Leave loose.

Tank Retainer Wire

Qty. 1
 Qty. 1

9

Parts to assemble:

- 1 LP Gas Tank
- 1 Tank Collar

LP tank is sold separately. Fill and leak check before attaching to grill and regulator.

A. Center LP tank on support bracket.
 B. Slide retainer over tank collar and tighten tie knob.

Tank Collar
 LP Gas Tank

CAUTION

Tank collar opening must face to front of cart once tank is attached.
 Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

See Use & Care manual to perform the "Burner Flame Check" and for important safety instructions before using.

10

Parts to assemble:

- 1 Grease Clip

A. Hang grease clip on front of grill.
 B. Hang an empty saw can (not included) from grease clip.

Rear view of grill.
 Grease Clip

CAUTION

* Failure to install can in clip will cause hot grease to be released from grill in the event of fire or property damage.