

MODEL	CA0516K	CA0616KR	CA0816KR	CA1016KR	CA1216KR	CA1516KR
<b>PERFORMANCE</b>						
<b>Cooling Area</b>	180	240	350	490	594	550-875
<b>BTUH Cooling</b>	5000	5850	7600	10000	12000	14250
<b>EER</b>	9.7	9.7	9.8	9.8	9.8	10.5
<b>Moisture Removal (pints/hr)</b>	1.5	1.75	2.35	2.94	3.58	3.6
<b>Room Air Delivery (CFM Max.)</b>	141	142	200	235	324	410
<b>ELECTRICAL</b>						
<b>Voltage</b>	115	115	115	115	115	115
<b>Amps Cooling</b>	4.8	5.4	7.6	9.5	11	12.3
<b>Watts Cooling</b>	515	600	775	1020	1220	1360
<b>Plug Capacity Amps.</b>	15 amp	15 amp	15 amp	15 amp	15 amp	15 amp
<b>Plug Type</b>	A	A	A	A	A	A
<b>FEATURES</b>						
<b>Air Exchanger</b>	No	No	Yes	Yes	Yes	No
<b>Air Direction</b>	2	2	4	4	4	6
<b>Fan Speed</b>	2	2	2	3	3	2
<b>Adjustable Thermostat</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Window Mount Type</b>	Included	Included	Included	Included	Included	Included
<b>Slide-Out Chassis</b>	No	Yes	Yes	Yes	Yes	Yes
<b>Slide-Out Filter</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>CABINET SIZE</b>						
<b>Width in. (mm)</b>	17.7 (450)	17.7 (450)	18.5 (470)	20.5 (521)	22.8 (579)	26.4 (671)
<b>Depth in. (mm)</b>	15.7 (399)	15.7 (399)	18.3 (465)	23.2 (589)	24 (610)	26.8 (681)
<b>Height in. (mm)</b>	12.4 (315)	12.4 (315)	13.8 (350)	14.8 (376)	15.7 (399)	17.5 (445)
<b>WINDOW OPENING</b>						
<b>Width Min. in. (mm)</b>	22 (559)	22 (559)	22.7 (577)	25.3 (643)	27.7 (704)	30 (762)
<b>Width Max. in. (mm)</b>	31.7 (805)	31.7 (805)	32.7 (831)	36.3 (922)	38.5 (978)	44 (1118)
<b>Height Min. in. (mm)</b>	13 (330)	13 (330)	14 (356)	16 (406)	16 (406)	18.5 (470)
<b>WEIGHT</b>						
<b>Net lbs. (kg)</b>	46 (21)	46 (21)	56 (25)	88.5 (40)	106 (48)	128 (58)
<b>Ship lbs. (kg)</b>	51 (23)	51 (23)	64 (29)	106 (48)	115 (52)	150 (68)
<b>SOUND LEVELS (dBA)</b>						
<b>Cooling (High)</b>	51	51	53	54	53	55
<b>Cooling (Medium)</b>	-	-	-	50	51	-
<b>Cooling (Low)</b>	49	49	50	47	49	50

All models feature LCDI Receptacle (Leakage - Current Detection and Interruption)

**Warranty:**

2 Year Repair or Replacement Limited Warranty



Due to ICP's commitment to product improvement, specifications and performance data subject to change without notice

© 2008 International Comfort Products Corporation (Canada) Printed in Canada Part No 000000



**PLUG TYPES**



15 amps  
125 volts



15 amps  
250 volts



20 amps  
250 volts



30 amps  
250 volts