


Hotpoint NKXR473ET5WW Owner's Manual


Shop genuine replacement parts for Hotpoint NKXR473ET5WW



Find Your Hotpoint Dryer Parts - Select From 384 Models

----- Manual continues below ------





800.626.2000



Welcome

Welcome to the **Hotpoint family**. We're proud of our quality products and we believe in dependable service. You'll see it in this easy-touse **manual** and you'll hear it in the part of your **family** for a long **time**. friendly voices of our customer service department.

Best of all, you'll experience these values each time you do the laundry. That's important, because your new dryer will be

Start Here!	Staple your receipt to the inside back cover of this manual.	Write down the model and serial
Refore	outei vi una mailuai.	numbers here. They are on the label on the front of the dryer behind
Dejute		the door.
Before using		
your		
your dryer		
-		

Model number

Serial number

Date of purchase

Need Help?

Hea us help you

800.626.2000

Before you call for service, there are a **few** things you can do to help us serve you better.

Read this manual. It contains **instructions** to help you use and maintain your dryer **properly.**

Saw time and money. Check the section titled "If Something Goes Wrong" before calling. This section was designed to solve common problems you might encounter.

If you do need service, you can relax knowing help is only a phone call away. A list of toll-free customer service numbers is included on the inside back cover. **Or call** the GE Answer **Center®** at 800.626.2000, 24 hours a day, 7 days a week.

Important Safety Information

Read all safety information before using

A warning: For your safety the information in this manual must be

followed to minimize the risk of fire or explosion or to prevent property damage, personal injury or loss of life.

Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.

Installation and service must be performed by a qualified installer, service agency or the gas supplier.

IF YOU SMELL GAS

 Do not try to light any appliance.
 Do not touch any electrical switch; do not use any phone in your building.

3 Clear the room, building or area of all occupants.
4 Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.

5 If you cannot reach your gas supplier, call the fire department.

California Safe Drinking Water and Toxic Enforcement Act

This act requires the governor of California to publish a list of substances known to the state to cause cancer, birth defects or other reproductive harm and requires businesses to warm customers of potential exposure to such substances. Cas appliances can cause minor exposure to four of these substances, namely benzene, carbon monoride, formaldehydes and soot, caused primarily by the incomplete combustion of natural gas or LP fuels.

Properly adjusted dryers will minimize incomplete combustion. Exposure to these substances can be minimized further by properly venting the dryer to the outdoors.



Important Safety Information

Read all safety information before using

Warning	
	To reduce the risk of fire, electric shock, or injury to persons when using your appliance, follow basic precautions, including the following sections.

Safety Precautions	 Use this appliance only for its intended purpose as described in this Owner's Manual. This dryer must be properly 	 Gas dryers MUST be exhausted to the outside. Carefully follow the Exhausting details in the Instigation Instructions.
	 installed and located in accordance with the Instigation Instructions before it is used. If you did not receive an Instigation Instructions sheet with your dryer, you can obtain one by calling, toll free, the GE Answer Center", 800.626.2000. 	 Exhausting electric dryers to the outside is STRONGLY RECOMMENDED to prevent large amounts of moisture and lint from being blown into the room. Carefully follow the Exhausting details in the Insolation Instructions.
	 Properly ground to conform with all governing codes and ordinances. Follow details in Installation Instructions. 	 Do not repair or replace any part of the appliance or attempt any servicing unless specifically recommended in this
	 - Install or store where the temperature is above 50°F. (10°C.). Do not install the-r where it will be exposed to the weather. 	Owner's Manual or in published user-repair instructions that you understand and have the skills to carry out.
	 Connect to a properly rated, protected and sized power supply circuit to avoid electrical overload. 	• When disconnecting this appliance pull by the plug rather than the cord to avoid damage to the cord or junction of cord and plug. Make sure that the cord is located so that it will not be

stepped on, tripped over or **otherwise** subjected to damage

or stress.

- Exhaust Duct–See Installation Instructions. Use only rigid metal or flexible metal 4" diameter ductwork inside the dryer cabinet or for exhausting to the outside. USE OF PLASTIC OR OTHER COMBUSTIBLE DUCTWORK CAN CAUSE A FIRE. PUNCTURED DUCTWORK CAN CAUSE A FIRE IF IT COL-LAPSES OR BECOMES OTHER-WISE RESTRICTED IN USE OR DURING INSTALLATION.
- . Do not dry articles containing rubber, plastic, or similar materials (such as padded bras, tennis shoes, galoshes, bath mats, rugs, bibs, baby pants, plastic bags, pillows, etc.) as these materials may melt or burn. Also, some rubber materials, when heated, can under certain circumstances produce fire by spontaneous combustion.
- Do not store items that may burn or melt (such as clothing, paper **material,** plastics or plastic containers, etc.) on top of the **dryer** during operation.
- **Garments** labeled "Dry Away from Heat" or **"Do** not Tumble **Dry"** (such as **life jackets** containing **Kapok)** must not be put in your dryer.

- Do not wash or dry articles that have been cleaned in, washed in, soaked in, or spotted with combustible or explosive substances (such as wax, paint, oil, gasoline, degreasers, drycleaning solvents, kerosene, etc.) which may ignite or explode. Do not add these substances to the wash water. Do not use these substances around your washer and/or dryer during operation.
- . Any article on which you have used a cleaning solvent, or which contains flammable materials (such as cleaning cloths, mops, towels used in beauty salons, restaurants, or barbershops, etc.) must not be placed in or near the dryer until all traces of these flammable liquids or solids and their fumes have been removed. There are many highly flammable items used in homes such as acetone, denatured alcohol, gasoline, kerosene, some household cleaners, some spot removers, turpentines, waxes, wax removers and products containing petroleum **distillates.**

Read all safety information before using

- Clean the lint filter before each load to prevent lint accumulation inside the **dryer** or in **the** room. DO NOT **OPERATE** THE **DRYER WITHOUT** THE **LINT FILTER** IN **PLACE.**
- . Keep the area **around and** underneath your appliances free **from** the accumulation of combustible **materials**, such as lint, paper, rags, **chemicals**, etc.
- The interior of the machine and the exhaust duct connection inside the **dryer** should be cleaned periodically

by a qualified individual.

- Never reach into the dryer while the drum is moving.
 Before loading, unloading or adding clothes, wait until the drum has completely stopped.
- Do not@ fiberglass articles in your *cr. Skin irritation could result **from** the remaining glass particles that may be picked up by **clothing** during **subsequent dryer** uses.
- The **laundry** process can reduce the flame **retardancy** of fabrics. To avoid such a **result,** the garment manufacturer's care instructions should be **followed very** carefully.

- Close supervision is necessary if this appliance is used by or near children. Do not allow children to play inside, on, or with this appliance or any discarded appliance. Dispose of discarded appliances and shipping or packing materials properly. Before discarding a dryer, or removing from service, remove the door of the dryer compartment.
- Keep **all** laundry aids (such as detergents, bleaches, fabric softeners, etc.) out of **the** reach of children, preferably in a locked cabinet. **Observe all** warnings on container labels to avoid personal **injury.**
- . **Keep the** floor around your appliances clean and **dry** to reduce the possibility of slipping.
- To **minimize** the possibility of electric shock, unplug this appliance from the power supply or disconnect the **dryer** at the household distribution panel by removing the fuse or switching off the circuit breaker before attempting any maintenance or cleaning (except the removal and cleaning of the lint filter).
- **NOTE:** Turning the Cycle Selector knob to an **OFF** position does NOT disconnect the appliance from the power supply.


Y

- Do not tamper with the controls.
- . **Do** not operate this appliance **if it** is damaged, **malfunctioning,** partially disassembled, or has missing or broken **parts,** including a damaged cord or plug.
- Never climb on or s-don the dryer top.
- If yours is a gas dryer, it is equipped with an automatic electric ignition and does not have a pilot light. DO NOT ATTEMPT TO LIGHT WITH A MATCH. Burns may result from having your hand in the vicinity of the burner when the automatic ignition may turn on.
- . You may wish to soften your laundered fabrics or reduce the static electricity in them by using **dryer-applied** fabric softeners or an antistatic conditioner. We recommend you use either a fabric softener in **the** wash **cycle**, according to the **manufacturer's** instructions for those products, or **try** a **dryer-added** product for which **the** manufacturer gives written assurance on the package that their product can be safely used in your dryer.

Service or performance **prob**lems caused by the use of **these** products are the responsibility of the manufacturers of those products and are not covered under **the warranty** of this appliance.

SAVE THESE INSTRUCTIONS

Operating Instructions





Clean the lint filter each time you use the dryer. CAUTION:

Do not operate the dryer without the lint filter in place.

${f A}$ Fabric Care Selections

Always follow Fabric Manufacturer's Care **Label** or instructions when laundering. Use this chart as a general guide.

Drying Selections	Usage
Cottons/High Heat	For regular to heavy cottons.
Perm, Press/Med, Heat	
	For synthetics, blends and items labeled "permanent press."
Knits Delicates/Low Heat	For delicates, synthetics and items labeled "tumble dry low."
Fluff/No Heat	For "fluffing" items without heat. Use the Timed Dry cycle.

Cycle Descriptions

Automatic Drying Cycles


Cycles automatically sense fabric dryness

Auto Perm. Press

For synthetic blends and delicates. Select **More Dry** for heavier loads, **Less Dry** for lighter loads.

Auto Cottons

For cottons and most linens. For most normal loads set at **auto cottons.** Set towards **More Dry** for heavier and wetter fabrics, **Less Dry** for lighter fabrics.





Select an automatic or timed **cycle.** See **the** above **Cycle** Descriptions.

Astarting Dryer

- Close the dryer door.
- Select START.

Opening **the** door during **the** operation till stop **the** @cr. To restart **the dryer, close the** door and select START to complete **the cycle.**

See next page for other dryer features

Timed Dry Cycles

Cycles run for a selected time

Timed Dry Set the Cycle Selector at the desired drying time.

Damp Dry

To leave items partially dry set Cycle Selector on Damp Dry setting.

Dewrinkle

For removing wrinkles from items that are clean and dry or that are very lightly damp. Set the Cycle Selector on the Dewrinkle setting.

NY YOU DE

NOTE:

Automatic drying times will vary according to the type of heat used (Electric, Natural or LP gas), size of load, types of fabrics, wetness of clothes and condition of exhaust ducts.

Other dryer features your model has

Press Guard




Use this option to **minimize** the **wrinkles** in clothes. **The** option provides approximatel, 15 minutes of **no-heat** tumbling after the clothes are dry.

This option can only be **used with** the Automatic cycles.

HINT:

If the Signal **option** is **selected**, the Signal **will sound at** the end of **the drying** time and **will sound several times during** the **Press Guard cycle**. **This** will **remind you** that the cycle is almost complete.

Signal



The signal control can be set at **OFF, MEDIUM** or LOUD.


This signal **will sound just** before the end of the cycle to remind you to remove the clothes.

If you selected the Press Guard option **the** signal **will** sound at the end of **the** drying time and till sound **several** times during the Press Guard cycle. **This will** remind you that the **cycle** is almost complete.

NOTE:

- Remove garments promptly at the sound of the signal. Place clothes on hangers w wrinkles won't set in.
- Use the Signal especially when drying fabrics like polyester knits and permanent press. These fabrics should be removed promptly so wrinkles wont set in.

Drum Lamp



Before replacing the light bulb, be sure to unplug the **dryer power** cord or disconnect the dryer at the household distribution panel by removing the fuse or **switching** off the circuit **breaker.** Reach above **dryer** opening from inside **the** drum. Remove the bulb and replace **with** the same **size** bulb.

Helpful Information

Specialty Care Guide

Always follow Fabric Manufacturer's Care Label or instructions when laundering. Otherwise use the information below as a general guide.

ltem	Suggested Care		
Pillows	Mend any holes or weak seams where feather or filling could escape. Dry only one pillow at a time. Stop dryer occasionally and shake pillow, redistributing falling for even drying. Check pillow at the end of drying time. If it is not completely dry, reset dryer for more drying time.		
	Dry on low heat only.		
	CAUTION: Do not dry pillows containing foam rubber.		
Blankets	Add 2-4 dry towels and one blanket and set timer for 2&25 minutes. Dry only one blanket at a time. Do not set control for more than 25 minutes. At the end of drying cycle block the blanket back to its original shape. Allow blanket to dry thoroughly before storing.		
Cotton	Use a medium heat drying setting.		
Synthetic	Use a low heat drying setting.		
Down	Use a low heat drying setting.		
Extra Large Items	Use a low heat drying setting.		
(Includes comforters, blankets and mattress pads.)	 Dry only one extra large item at a time. Set dryer for 20 minutes. When time is up, check and redistribute load. Reset dryer and check after 15 minutes. When time is up, check and redistribute load. Reset timer and check at 5 minute intervals. Check after each 5 minutes to ensure articles do not fill dryer drum. Large, wet articles should have ample room in the dryer, but as they dry and fluff up they may not have room to tumble. CAUTION: Items without room to tumble may block airflow and 		
	could result in scorched items. Dry mattress pads separately. Use a low heat drying setting.		

Loading

Sorting

As a general rule, if clothes are sorted **properly for** the washer, they are sorted **properly** for the dryer.

Sort by color

(Separate colorfast from non-colorfast fabrics*)

- Whites
- Lights
- Darks

Separate by fabric type

- Cottons and linens
- Permanent press cottons and blends
- Synthetic and poly knits
- Delicates

Separate lint producers from lint collectors

- Lint producers: terry cloth and chenille
- Lint collectors: velveteen and corduroy

Sort by weight

- Heavy Items
- Light Items
- * Non-colorfast fabrics may bleed or fade. Sort by individual color.

Loading Hints

- Avoid drying very small loads.
- Sort clothes by weight so you won't have to **run** an **extra cycle** for one or two heavier, slower **drying items.**
- Do not add fabric softener sheets once the load has become warm.
 This may cause fabric softener stains.
- Do not overload. **This** causes inefficient operation and **unnecessary wrinklig.** Clothes need to tumble **freely.**

- Do not dry the following items:
 - . Fiberglass items
 - Woolens
 - . Rubber **coated items**
 - Plastics
 - $1 \sim$ with plastic trim Foam-filled items

Care & Cleaning

Interior

The drum is **rust-resistant. However,** colored fabrics which lose color or bleed in **the washer** may cause **dis**coloration of the-r drum. We recommend that the **dryer** drum be **cleaned with** a **cloth** using a


detergent and water paste or a mild abrasive, such as Soft Scrub™. Rinse thoroughly. Then tumbledry several wet rags or old towels for 20 to 30 minutes before using the dryer normally.

Exterior

Wipe off any **spills** or washing compounds. Wipe or dust with a damp cloth. **Try** not to strike the **surface with** sharp objects. Dryer control panel and **finishes** may be damaged by some **laundry pretreatment soil** and stain **remover products** if **such** products **are** sprayed on or **have** direct contact with **the dryer**.

Apply these pretreatment **products** away **from** the dryer. The **fabric** may **then** be washed and dried normally. Damage **to** your **dryer** caused by **pretreatment** products is not **covered** by your **warranty**.

Lint Filter



Before every dryer use, clean the lint filter. It is easier to remove the lint when your fingers are moistened.


To keep your dryer operating at peak performance, be sure to have a technician vacuum the lint from the machine every three years.

Storage

To store your **dryer for a** short period of time, disconnect the power supply and clean the **lint filter.** i

Helpful Information


Exhaust Duct



Inspect and **clean** the dryer **exhaust ducting** at least once a year to **prevent clogging.** A **partially clogged exhaust** can lengthen the drying time. To clean **the exhaust** duct follow **these** steps:

- 1 Turn off electrical supply by disconnecting the plug from the wall socket.
- **2** Disconnect **exhaust duct from** the **dryer.**
- 3 Vacuum the exhaust duct with the hose attachment.
- 4 Reconnect the exhaust duct to the dryer.

Exhaust Hood



C eck the side of the exhaust hood with a m mor to rid of debris

- Make sure the inside flaps of the exhaust hood move freely (you may want to check with a mirror).
- Make sure inside **flaps** are **fully** open when dryer is operating.
- Make sure there is not wild life (birds, insects, etc.) nesting inside the exhaust duct or hood.

If Something Goes Wrong

Before you call for service



Problem	Possible Causes	What to Do
Dryer doesn't start	Dryer is unplugged	. Make sure the dryer plug is pushed completely into the outlet.
	Fuse is blown/circuit breaker is tripped	• Check the house fuse/circuit breaker box and replace fuse or reset breaker. NOTE: Most electric dryers use two breakers.
Dryer doesn't heat		
	Fuse is blown/circuit breaker is tripped, the dryer may tumble but not heat	• Check the house fuse/circuit breaker box and replace fuse or reset breaker.
	Gas service is off	• Make sure gas shutoff at dryer and main shutoff are fully open.
Dryer shakes or makes excessive nois	Some shaking/noise is normal. Dryer may be sitting unevenly	• Move dryer to an even floor space, or adjust as necessary until even.
Greasy spots on clothe	es Improper use of fabric softener	• Follow directions on fabric softener package.
	Drying dirty items with clean ones	• Use your dryer to dry only clean items. Dirty items can stain clean items and the dryer.
	Clothes were not completely clean	• Sometimes stains which cannot be seen when the clothes are wet "appear" after drying. Use proper washing procedures before drying.
Lint on clothes	Lint filter is full	• Clean lint screen before each load.
	Improper sorting	• Sort lint producers (like chenille) from lint collectors (like corduroy).
	Static electricity can attract lint	• See suggestions in this section under STATIC.
	Overloading	• Separate large loads into smaller ones.
	Paper, tissue, etc. left in pockets	• Empty all pockets before laundering clothes.

If Something Goes Wrong

?

Problem	Possible Causes	What to Do
Static occurs	Overdrying	• Try a fabric softener. • Adjust controls for less drying.
	No fabric softener was used	• Try a fabric softener.
	Synthetics, permanent press and blends can cause static	. T_{ry a fabric softener.}
Clothes take too long to dry	Improper sorting	• Separate heavy items from light weight items (generally, a well-sorted washer load is a well-sorted dryer load).
	Large loads of heavy items (like beach towels)	•Large, heavy loads contain more moisture and take longer to dry. Separate large, heavy items into smaller loads to speed drying time.
	Controls improperly set	. Match control settings to the load you are drying.
	Lint filter is full	• Clean lint filter before every load.
	Improper or obstructed ducting	. Check instigation instructions for proper ducting/venting.
		• Make sure ducting is clean, free of kinks and unobstructed.
		. Check to see if outside wall damper operates easily.
		•See the Venting the Dryer section.
	Blown fuses or tripped circuit breakers	• Replace fuses or reset circuit breakers. Since most dryers use 2 fuses/breakers, make sure both are operating.
	Overloading/ combining loads	• Do not put more than one-her load in the dryer at a time.
	Underloading	• If You are drying only one or two items, add a few items to ensure proper tumbling.

?


Problem	Possible Causes	What to Do
Clothes are wrinkled	Overdrying	• Select a shorter drying time.
		• Remove items while they still hold a slight amount of moisture.
	Letting items sit in dryer after cycle ends	• Remove items when cycle ends and fold or hang immediately.
Clothes shrink Some fabrics will naturally shrink when washed. Others	• To avoid shrinkage, follow garment care labels exactly.	
	can be safely washed, but will shrink in the dryer.	 Some items may be pressed back into shape after drying.
		• If you are concerned about shrinkage in a particular item, do not machine wash or tumble dry it.

Venting the Dryer


For the best drying **performance the** dryer needs to be properly vented. **Carefully follow the details on Exhausting** in **the Installation Instructions.**

- Use only rigid metal or flexible metal 4" diameter ductwork inside the dryer cabinet or for exhausting to the outside.
- Do not use **plastic** or **other** combustible **ductwork**.
- Use the shortest length possible.
- . Do not-h or collapse.
- Avoid resting the duct on sharp objects.
- Venting must conform to local building codes.


Correct Venting








Incorrect Venting





Notes

Notes

-

_

Notes

Hotpoint Service Numbers

We'll be there!

GE Answer Center 800.626.2000	Whatever your question about any Hotpoint major appliance, GE Answer Center [®] information ser- vice is available to help. Your call- and your question-will be answered promptly and courteously.	And you can call any time. GE Answer Center" service is open 24 hours a day, 7 days a week.
In-Home Repair Service 800-GE-CARES (800-432-2737)	A GE consumer service professional will provide expert repair service, scheduled at a time that's conve- nient for you. Many GE Consumer Service company-operated loca- tions offer you service today or tomorrow, or at your convenience (7:00 am. to 7:00 p.m. weekdays, 9:00 a.m. to 2:00 p.m. Saturdays).	Our factory-trained technicians know your appliance inside and out-so most repairs can be han- dled in just one visit.

For Customers With Special Needs

800.626.2000

Upon **request, GE will** provide **Braille controls for a variety** of **GE appliances, and a brochure to assist in planning a barrier-free kitchen** for **persons with limited mobility.** To obtain these **items, free of charge, call** 800.626.2000.

Consumers with impaired hearing or speech who have access to a **TDD or a convention teletype**writer may call 800-TDD-GEAC (800-833-4322) to request informa tion or service.

Service Contracts 800-626-2224	You can have the secure feeling that GE Consumer Service till still be there after your warranty expires. Purchase a GE contract while your warranty is still in effect and you'll receive a substantial discount. With a multiple-year contract, you're assured of future service at today's prices.		
Parts and Accessories	Individuals qualified to service their own appliances can have parts or accessories sent directly to their home. The GE parts system provides access to over 47,000 partsand all GE Genuine Renewal Parts are fully warranted. VISA, MasterCard and Discover cards are accepted.	Care and cleaning instructions con- tained in this manual cover proce- dures to be performed by any user. Other servicing generally should be referred to qualified service person- nel. Caution must be exercised, since improper servicing may cause unsafe operation.	
Further Service	We're proud of our service and want you to be pleased. If for some reason you are not happy with the service you receive, here are three steps to follow for further help. First, contact the people who ser- viced your appliance. Explain why you are not pleased. In most cases, this will solve the problem. Mext, if you are still not pleased, write all the details—including your phone number-to: Manager, Consumer Relations Hotpoint Appliances, Appliance Park Louisville, KY 40225	Finally, if your problem is still not resolved, write: Major Appliance Consumer Action Program 20 North Wacker Drive Chicago, IL 60606	

DRYER WARRANTY

Staple sales slip or cancelled check here. Proof of original purchase date is needed to obtain service under warranty.

///hot	10	covered	
VIIAI		1 - 1 1 1 / 6 - 1 1 5 - 1 1	
	10	$\circ \circ $	

FULL ONE-YEAR WARRANTY

For one year from date of original purchase, we will provide, free of charge, parts and service labor in your home to repair or replace *any part of the dryer* that fails because of a manufacturing defect.

LIMITED ADDITIONAL FOUR-YEAR WARRANTY

From the second **through fifth** year from date of original purchase, we will replace, free of charge, an extra large or super capacity dryer drum that fails because of a manufacturing defect. You pay for the service trip to your home and service labor charges.

This warranty is extended to the origina purchaser and any Succeeding owner for products purchased for ordinary home use in the* mainland states, Hawaii an Washington, D.C. In Alaska the warrant is the same except that it is LIMITED because you must pay to ship the product to the service shop or for the service technician's travel costs to your home.

All warranty service will be provided by our Factory Service Centers or by our authorized Customer Care[®] servicers during normal working hours.

Should your appliance need service, during warranty period or beyond, call 800-GE-CARES (800-432-2737).

What is not covered

• Service trips to your home to teach you how to use the product.

Read your Owner's - A **If you** then have any questions about operating the product, please contact your **dealer** or our **Consumer Affairs** office at the address below, or **call, toll** free:

GE Answer Center" 800.626.2000 consumer information service

• Improper installation.

If you have an installation problem, contact your dealer or installer. You ar responsible for providing adequate electrical, exhausting and other connecting facilities.

- . **Replacement** of house **fuses** or resetting of **circuit breakers**.
- Failure of the product if it is misused, or used for other than the intended
 - purpose or used commercially.
- Damage to product caused by accident, fire, floods or acts of God.

WARRANTOR IS NOT RESPONSIBLE FOR CONSEQUENTIAL DAMAGES.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warrantygives you specific legal rights, and you may also have other rights which vary from state to state. To know what your legal rights are in your state, consult your local or state consumer affairs office or your state's Attorney General. Warrantor: General Electric Company If further help is needed concerning this warranty, writes Manager-Consumer Affairs, GE Appliances, Louisville, KY 40225

Part No. 175D1807P085 Pub. No. 39-9332

CG

Printed in Canada

NWXR473ET NWXR475. NKXR473ET NKXR473G1