


Hotpoint NWXR473ET5WB Owner's Manual

Shop genuine replacement parts for Hotpoint NWXR473ET5WB



Find Your Hotpoint Dryer Parts - Select From 384 Models

----- Manual continues below -----

Models: NWXR473ET NKXR473ET NWXR473GT NKXR473GT



Y	Important Safety Information	3
	Operating Instructions The Co-is on Your Dryer Other Dryer Features	8
	Helpful Information Specialized Fabric Guide Loading Suggestions Care of Product	11
?	If Something Goes Wrong Before You till For Service Venting the Dryer Hotpoint Service Numbers Warranty, Back Corer	15

GE Answer Center® 800.626.2000

HOTPOINT

Welcome

Welcome to the **Hotpoint family.** We're proud of our quality products and we believe in dependable service. You'll see it in this easy-touse manual and you'll hear it in the part of your family for a long time. friendly voices of our customer service department.


Best of all, you'll experience these values each time you do the laundry. That's important, because your new dryer will be

Start Here!

Before

Staple your receipt to the inside back cover of this manual.

Write down the model and serial numbers here. They are on the label on the **front** of the **dryer** behind the door.



Model number

Serial number

Date of purchase

Need Help?

He@ us help you

800,626,2000

Before you call for service, there are a **few** things you can do to help us serve you better.

Read this manual. It contains instructions to help you use and maintain your dryer properly.

Saw time and money. Check the section titled "If Something Goes Wrong" before calling. This section was designed to solve common problems you might encounter.

If you do need **service**, you can relax knowing help is only a phone call away. A list of toll-free customer service numbers is included on the inside back cover. Or call the GE Answer **Center** at 800.626.2000, 24 hours a day, 7 days a week.

Important Safety Information

Read all safety information before using

WARNING: For your safety the information in this manual must be followed to minimize the risk of fire or explosion or to prevent property damage, personal injury or loss of life.

Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.

Installation and service must be performed by a qualified installer, service agency or the gas supplier.

IF YOU SMELL GAS.

- 1 Do not try to light any appliance.
- 2 Do not touch any electrical switch; do not use any phone in your building.
- 3 Clear the room, building or area of all occupants.
- Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.
- If you cannot reach your gas supplier, call the fire department.

A California Safe Orinking Water and Toxic Enforcement Act

This act requires the governor of California to publish a list of substances known to the state to cause cancer, birth defects or other reproductive harm and requires businesses to warn customers of potential exposure to such substances.

Gas appliances can cause:

minor exposure to four of these
substances, namely benzene.

carbon monoxide, formaldehyde
and soot, caused primarily by the
incomplete combustion of natural
gas or LP fuels.

Properly adjusted dryers will minimize incomplete combustion. Exposure to these substances can be minimized further by properly venting the dryer to the outdoors.



Important Safety Information

Read all safety information before using

Marning

To reduce the risk of fire, electric shock, or injury to persons when using your appliance, follow basic precautions, including the following sections.

Safety Precautions

- Use this appliance only for its intended purpose as described in this Owner's Manual.
- This dryer must be properly installed and located in accordance with the Instigation Instructions before it is used.
 If you did not receive an Instigation Instructions sheet with your dryer, you can obtain one by calling, toll free, the GE Answer Center", 800.626.2000.
- Properly ground to conform with all governing codes and ordinances. Follow details in Installation Instructions.
- Install or store where the temperature is above 50°F. (10°C.). Do not install the-r where it will be exposed to the weather.
- Connect to a properly rated, protected and **sized** power supply circuit to avoid **electrical** overload.

- Gas dryers MUST be exhausted to the outside. Carefully follow the Exhausting details in the Instigation Instructions.
- Exhausting electric dryers to the outside is STRONGLY
 RECOMMENDED to prevent large amounts of moisture and lint from being blown into the room. Carefully follow the
 Exhausting details in the Insolation Instructions.
- Do not repair or replace
 any part of the appliance or
 attempt any servicing unless
 specifically recommended in this
 Owner's Manual or in published
 user-repair instructions that you
 understand and have the skills
 to carry out.
- When disconnecting this appliance pull by the plug rather than the cord to avoid damage to the cord or junction of cord and plug. Make sure that the cord is located so that it will not be stepped on, tripped over or otherwise subjected to damage or stress.



- Exhaust **Duct—See** Installation
 Instructions. Use only rigid **metal**or flexible **metal** 4" **diameter**ductwork inside the **dryer** cabinet
 or for exhausting to the **outside**.
 USE OF **PLASTIC** OR OTHER **COMBUSTIBLE DUCTWORK CAN CAUSE** A **FIRE**.
 PUNCTURED **DUCTWORK**CAN **CAUSE A FIRE IF IT COL- LAPSES** OR BECOMES **OTHER- WISE RESTRICTED IN** USE OR **DURING INSTALLATION**.
- . **Do not dry** articles **containing** rubber, plastic, or similar materials (such as padded **bras**, tennis shoes, **galoshes**, bath **mats**, rugs, bibs, baby pants, plastic bags, **pillows**, etc.) as **these** materials may melt or burn. Also, some rubber materials, when heated, can under **certain** circumstances produce fire by spontaneous combustion.
- Do not store items that may burn or melt (such as clothing, paper **material**, plastics or plastic containers, etc.) on top of the **dryer** during operation.
- Garments labeled "Dry Away from Heat" or "Do not Tumble Dry" (such as life jackets containing Kapok) must not be put in your dryer.

- **Do not wash** or **dry** articles **that** have been cleaned in, **washed** in, soaked in, or spotted with combustible or explosive **substances** (such **as wax,** paint, oil, gasoline, **degreasers, dry**-cleaning solvents, kerosene, etc.) which may ignite or explode. Do not add these substances to the wash water. Do not use these **substances** around your washer and/or **dryer** during operation.
- . **Any** article on which you **have** used a cleaning solvent, or which contains flammable materials (such as cleaning cloths, mops, towels used in beauty salons, restaurants, or barbershops, etc.) must not be placed in or near the dryer until all traces of these flammable liquids or solids and their fumes have been removed. There are many highly flammable items used in homes such as acetone, denatured alcohol, gasoline, kerosene, some household cleaners, some spot removers, turpentines, waxes, wax removers and products containing petroleum distillates.



Important Safety Information

Read all safety information before using

- Clean the lint filter before each load to prevent lint accumulation inside the dryer or in the room. DO NOT OPERATE THE DRYER WITHOUT THE LINT FILTER IN PLACE.
- . Keep the area **around and** underneath your appliances free **from** the accumulation of combustible **materials**, such as lint, paper, rags, **chemicals**, etc.
- The interior of the machine and the exhaust duct connection inside the **dryer** should be cleaned periodically by a qualified individual.
- Never reach into the dryer while the drum is moving.
 Before loading, unloading or adding clothes, wait until the drum has completely stopped.
- Do not@ fiberglass articles in your *cr. Skin irritation could result from the remaining glass particles that may be picked up by clothing during subsequent dryer uses.
- The laundry process can reduce the flame retardancy of fabrics. To avoid such a result, the garment manufacturer's care instructions should be followed very carefully.

- Close **supervision** is necessary if this appliance is used by or near children. Do not allow children to play inside, on, or with this appliance or any discarded appliance. Dispose of discarded appliances and shipping or packing materials properly. **Before** discarding a **dryer**, or removing from **service**, remove **the** door of the **dryer** compartment.
- Keep **all** laundry aids (such as detergents, bleaches, fabric softeners, etc.) out of **the** reach of children, preferably in a locked cabinet. **Observe all** warnings on container labels to avoid personal **injury.**
- . **Keep the** floor around your appliances clean and **dry** to reduce the possibility of slipping.
- To **minimize** the possibility of electric shock, unplug this appliance from the power supply or disconnect the **dryer** at the household distribution panel by removing the fuse or switching off the circuit breaker before attempting any maintenance or cleaning (except the removal and cleaning of the lint filter).
- **NOTE:** Turning the Cycle Selector knob to an **OFF** position does NOT disconnect the appliance from the power supply.




- Do not tamper with the controls.
- . Do not operate this appliance if it is damaged, malfunctioning, partially disassembled, or has missing or broken parts, including a damaged cord or plug.
- Never climb on or s-don the dryer top.
- •If yours is a gas dryer, it is equipped with an automatic electric ignition and does not have a pilot light. DO NOT ATTEMPT TO LIGHT WITH A MATCH. Burns may result from having your hand in the vicinity of the burner when the automatic ignition may turn on.
- . You may wish to soften your laundered fabrics or reduce the static electricity in them by using **dryer-applied** fabric softeners or an antistatic conditioner. We recommend you use either a fabric softener in **the** wash **cycle**, according to the **manufacturer's** instructions for those products, or **try** a **dryer-added** product for which **the** manufacturer gives written assurance on the package that their product can be safely used in your dryer.
 - **Service** or performance **problems** caused by the use of **these** products are the responsibility of the manufacturers of those products and are not covered under **the warranty** of this appliance.

SAVE THESE INSTRUCTIONS

Operating Instructions



The controls on your dryer



A Clean the Lint Filter

Clean the lint filter each time you use the dryer. **CAUTION:**

Do not operate the dryer without the lint filter in place.

A Fabric Care Selections

Always follow Fabric Manufacturer's Care Label or instructions when laundering. Use this chart as a general guide.

Drying Selections	Usage
Cottons/High Heat	For regular to heavy cottons.
Perm. Press/Med. Heat	For synthetics, blends and items labeled "permanent press."
Knits Delicates/Low Heat	For delicates, synthetics and items labeled "tumble dry low."
Fluff/No Heat	For "fluffing" items without heat. Use the Timed Dry cycle.

Cycle Descriptions



Automatic Drying Cycles Cycles automatically sense fabric dryness

Auto Perm. Press

For synthetic blends and delicates.
Select **More Dry** for heavier loads, **Less Dry** for lighter loads.

Auto Cottons

For cottons and most linens. For most normal loads set at **auto cottons**. Set towards **More Dry** for heavier and wetter fabrics, **Less Dry** for lighter fabrics.

Timed Dry Cycles

Cycles run for a selected time

Timed Dry

Set the Cycle Selector at the desired drying time.

Damp Dry

To leave items partially dry set Cycle Selector on Damp Dry setting.


Dewrinkle

For removing wrinkles from items that are clean and dry or that are very lightly damp. Set the Cycle Selector on the Dewrinkle setting.

k Water Water

NUTE:

Automatic drying times will vary according to the type of heat used (Electric, Natural or LP gas), size of load, types of fabrics, wetness of clothes and condition of exhaust ducts.



A Selecting Drying Cycle

Select an automatic or timed **cycle.** See **the** above **Cycle** Descriptions.

AStarting Dryer

- Close **the dryer** door.
- Select START.


Opening **the** door during **the** operation till stop **the** @cr. To restart **the dryer, close the** door and select START to complete **the cycle.**

See next page for other dryer features

Operating Instructions

Other dryer features your model has

Press Guard




Use this option to **minimize** the wrinkles in clothes. The option provides approximatel, 15 minutes of **no-heat** tumbling after the clothes are dry.

This option can only be used with the Automatic cycles.

HINT:

If the Signal option is selected, the Signal will sound at the end of the drying time and will sound several times during the Press Guard cycle. This will remind you that the cycle is almost complete.

Signal



The signal control can be set at **OFF, MEDIUM** or LOUD.


This signal will sound just before the end of the cycle to remind you to remove the clothes.

If you selected the Press Guard option **the** signal **will** sound at the end of **the** drying time and till sound **several** times during the Press Guard cycle. This will remind you that the **cycle** is almost complete.

NOTE:

- Remove garments promptly at the sound of the signal. Place clothes on hangers w wrinkles won't set in.
- Use the Signal especially when drying fabrics like polyester knits and permanent press. These fabrics should be removed promptly so wrinkles wont set in.

Drum Lamp



Before replacing the light bulb, be sure to unplug the **dryer power** cord or disconnect the dryer at the household distribution panel by removing the fuse or switching off the circuit breaker. Reach above **dryer** opening from inside the drum. Remove the bulb and replace with the same size bulb.

Helpful Information

Specialty Care Guide



Always follow Fabric Manufacturer's Care Label or instructions when laundering. Otherwise use the information below as a general guide.

Item	Suggested Care			
Pillows	Mend any holes or weak seams where feather or filling could escape. Dry only one pillow at a time. Stop dryer occasionally and shake pillow, redistributing falling for even drying . Check pillow at the end of drying time. If it is not completely dry , reset dryer for more drying time.			
	Dry on low heat only.			
	CAUTION: Do not dry pillows containing foam rubber.			
Blankets	Add 2-4 dry towels and one blanket and set timer for 2&25 minutes. Dry only one blanket at a time. Do not set control for more than 25 minutes. At the end of drying cycle block the blanket back to its original shape. Allow blanket to dry thoroughly before storing.			
Cotton	Use a medium heat drying setting.			
Synthetic	Use a low heat drying setting. Use a low heat drying setting.			
Down				
Extra Large Items	Use a low heat drying setting.			
(Includes comforters, blankets and mattress pads.)	Dry only one extra large item at a time. Set dryer for 20 minutes. When time is up , check and redistribute load. Reset dryer and check after 15 minutes. When time is up, check and redistribute load. Reset timer and check at 5 minute intervals. Check after each 5 minutes to ensure articles do not fill dryer drum. Large , wet articles should have ample room in the dryer , but as they dry and fluff up they may not have room to tumble. CAUTION: Items without room to tumble may block airflow and			
	could result in scorched items. Dry mattress pads separately. Use a low heat drying setting.			

Helpful Information

Loading

Sorting

As a general rule, if clothes are sorted **properly for** the washer, they are sorted **properly** for the dryer.

Sort by color

(Separate colorfast from non-colorfast fabrics*)

- Whites
- Lights
- Darks

Separate by fabric type

- Cottons and linens
- Permanent press cottons and blends
- Synthetic and poly knits
- Delicates

Separate lint producers from lint collectors

- Lint producers: terry cloth and chenille
- Lint collectors: velveteen and corduroy

Sort by weight

- Heavy Items
- Light Items
- * Non-colorfast fabrics may bleed or fade. Sort by individual color.

Loading Hints

- Avoid drying very small loads.
- Sort clothes by weight so you
 won't have to run an extra cycle
 for one or two heavier, slower
 drying items.
- Do not add fabric softener sheets once the load has become warm.
 This may cause fabric softener stains.
- Do not overload. This causes inefficient operation and unnecessary wrinkling. Clothes need to tumble freely.

- Do not dry the following items:
 - . **Fiberglass** items
 - Woolens
 - . Rubber coated items
 - Plastics
 - 1~~ with plastic trim
 - . Foam-filled items

Care & Cleaning



Interior

The drum is **rust-resistant.** However, colored fabrics which lose color or bleed in **the washer** may cause **dis**-coloration of the-r drum. We recommend that the **dryer** drum be **cleaned with** a **cloth** using a

detergent and water paste or a mild abrasive, such as Soft Scrub™.


Rinse thoroughly. Then tumble-dry several wet rags or old towels for 20 to 30 minutes before using the dryer normally.

Exterior

Wipe off any **spills** or washing compounds. Wipe or dust with a damp cloth. **Try** not to strike the **surface with** sharp objects. Dryer control panel and **finishes** may be damaged by some **laundry pretreatment soil** and stain **remover products** if **such** products **are** sprayed on or **have** direct contact with **the dryer**.

Apply these pretreatment **products** away **from** the dryer. The **fabric** may **then** be washed and dried normally. Damage **to** your **dryer** caused by **pretreatment** products is not **covered** by your **warranty**.

Lint Filter



Before every dryer use, clean the lint filter. It is easier to remove the lint when your fingers are moistened.


To keep your dryer operating at peak performance, be sure to have a technician vacuum the lint from the machine every three years.

Storage

To store your **dryer for a** short period of time, disconnect the power supply and clean the **lint filter.**

Helpful Information

Exhaust Duct




Inspect and clean the dryer exhaust ducting at least once a year to prevent clogging. A partially clogged exhaust can lengthen the drying time.

To clean **the exhaust** duct follow **these** steps:

- 1 Turn off electrical supply by disconnecting the plug from the wall socket.
- 2 Disconnect exhaust duct from the dryer.
- 3 Vacuum the exhaust duct with the hose attachment.
- 4 Reconnect the exhaust duct to the dryer.

Exhaust Hood



C eck the side of the exhaust hood with a m rror to rid of debris

- Make sure the inside flaps of the exhaust hood move freely (you may want to check with a mirror).
- Make sure inside flaps are fully open when dryer is operating.
- Make sure there is not wild life (birds, insects, etc.) nesting inside the exhaust duct or hood.

If Something Goes Wrong

Before you call for service



Problem	Possible Causes	What to Do		
Dryer doesn't start	Dryer is unplugged	. Make sure the dryer plug is pushed completely into the outlet.		
	Fuse is blown/circuit breaker is tripped	 Check the house fuse/circuit breaker box and replace fuse or reset breaker. NOTE: Most electric dryers use two breakers. 		
Dryer doesn't heat	Fuse is blown/circuit breaker is tripped, the dryer may tumble but not heat	• Check the house fuse/circuit breaker box and replace fuse or reset breaker.		
	Gas service is off	 Make sure gas shutoff at dryer and main shutoff are fully open. 		
Dryer shakes or makes excessive noise	Some shaking/noise is normal. Dryer may be sitting unevenly	Move dryer to an even floor space, or adjust as necessary until even.		
Greasy spots on clothes	Improper use of fabric softener	Follow directions on fabric softener package.		
	Drying dirty items with clean ones	 Use your dryer to dry only clean items. Dirty items can stain clean items and the dryer. 		
	Clothes were not completely clean	 Sometimes stains which cannot be seen when the clothes are wet "appear" after drying. Use proper washing procedures before drying. 		
Lint on clothes	Lint filter is full	Clean lint screen before each load.		
	Improper sorting	• Sort lint producers (like chenille) from lint collectors (like corduroy).		
	Static electricity can attract lint	• See suggestions in this section under STATIC.		
	Overloading	• Separate large loads into smaller ones.		
	Paper, tissue, etc. left in pockets	Empty all pockets before laundering clothes.		

If Something Goes Wrong

Problem	Possible Causes	What to Do
Static occurs	Overdrying	Try a fabric softener.Adjust controls for less drying.
	No fabric softener was used	• Try a fabric softener.
	Synthetics, permanent press and blends can cause static	. Try a fabric softener.
Clothes take too long to dry	Improper sorting	• Separate heavy items from light weight items (generally, a well-sorted washer load is a well-sorted dryer load).
	Large loads of heavy items (like beach towels)	• Large, heavy loads contain more moisture and take longer to dry. Separate large, heavy items into smaller loads to speed drying time.
	Controls improperly set	. Match control settings to the load you are drying.
	Lint filter is full	Clean lint filter before every load.
	Improper or obstructed ducting	. Check instigation instructions for proper ducting/venting.
	•	 Make sure ducting is clean, free of kinks and unobstructed.
		. Check to see if outside wall damper operates easily.
		• See the Venting the Dryer section.
	Blown fuses or tripped circuit breakers	 Replace fuses or reset circuit breakers. Since most dryers use 2 fuses/breakers, make sure both are operating.
	Overloading/ combining loads	 Do not put more than one-her load in the dryer at a time.
	Underloading	• If You are drying only one or two items, add a few items to ensure proper tumbling.

Possible Causes	What to Do		
Overdrying	• Select a shorter drying time.		
	 Remove items while they still hold a slight amount of moisture. 		
Letting items sit in dryer after cycle ends	• Remove items when cycle ends and fold or hang immediately.		
Some fabrics will naturally shrink when washed. Others	• To avoid shrinkage, follow garment care labels exactly.		
can be safely washed, but will shrink in the dryer.	 Some items may be pressed back into shape after drying. 		
	 If you are concerned about shrinkage in a particular item, do not machine wash or tumble dry it. 		
	Overdrying Letting items sit in dryer after cycle ends Some fabrics will naturally shrink when washed. Others can be safely washed, but will		


? If Something Goes Wrong


Venting the Dryer

For the best drying performance **the** dryer needs to be properly vented. Carefully follow the details on Exhausting in the Installation Instructions.


- Use only rigid metal or flexible metal 4" diameter ductwork inside the dryer cabinet or for exhausting to the outside.
- Do not use plastic or other combustible ductwork.
- Use the shortest length possible.
- . Do not-h or collapse.
- Avoid resting the duct on sharp objects.
- Venting must conform to local building codes.


Correct Venting





Incorrect Venting





Notes			
	-		

Notes			
	-		

Votes		

7.

Hotpoint Service Numbers

We'll be there!

GE Answer Center

800.626.2000

Whatever your question about any Hotpoint major appliance, GE Answer Center information service is available to help. Your call—and your question—will be answered promptly and courteously.

And you can call any time. GE Answer Center" service is open 24 hours a day, 7 days a week.

In-Home Repair Service

800-GE-CARES (800-432-2737) A GE consumer service professional will provide expert repair service, scheduled at a time that's convenient for you. Many GE Consumer Service company-operated locations offer you service today or tomorrow, or at your convenience (7:00 am. to 7:00 p.m. weekdays, 9:00 a.m. to 2:00 p.m. Saturdays).

Our factory-trained technicians know your appliance inside and out—so most repairs can be han-\(^\)dled in just one visit.

For Customers With Special Needs

800.626.2000

Upon request, GE will provide Braille controls for a variety of GE appliances, and a brochure to assist in planning a barrier-free kitchen for persons with limited mobility. To obtain these items, free of charge, call 800.626.2000. Consumers with impaired hearing or speech who have access to a TDD or a convention teletypewriter may call 800-TDD-GEAC (800-833-4322) to request information or service.

Service Contracts

800-626-2224

You can have the secure feeling that GE Consumer Service till still be there after your warranty expires. Purchase a GE contract while your warranty is still in effect and you'll receive a substantial discount. With a multiple-year contract, you're assured of future service at today's prices.

Parts and Accessories

800-626-2002

Individuals qualified to service their own appliances can have parts or accessories sent directly to their home. The GE parts system provides access to over 47,000 parts...and all GE Genuine Renewal Parts are fully warranted. VISA, MasterCard and Discover cards are accepted.

Care and cleaning instructions contained in this manual cover procedures to be performed by any user. Other servicing generally should be referred to qualified service personnel. Caution must be exercised, since improper servicing may cause unsafe operation.

Further Service

We're proud of our service and want you to be pleased. If for some reason you are not happy with the service you receive, here are three steps to follow for further help.

First, contact the people who serviced your appliance. Explain why you are not pleased. In most cases, this will solve the problem.

Next, if you are still not pleased, write all the details—including your phone number-to:

Manager, Consumer Relations
Hotpoint Appliances,
Appliance Park
Louisville, KY 40225

Finally, if your problem is still not resolved, write:

Major Appliance Consumer Action Program 20 North Wacker Drive Chicago, IL 60606

DRYER WARRANTY

Staple sales slip or cancelled check here. Proof of original purchase date is needed to obtain service under warranty.

What is covered

FULL ONE-YEAR WARRANTY

For one year from date of original purchase, we will provide, free of charge, parts and service labor in your home to repair or replace any part of the dryer that fails because of a manufacturing defect.

LIMITED ADDITIONAL FOUR-YEAR WARRANTY

From the second **through fifth** year from date of original purchase, we will replace, free of charge, an extra large or super capacity dryer drum that fails because of a manufacturing defect. You pay for the **service** trip to your home and **service** labor charges.

This warranty is extended to the origina purchaser and any Succeeding owner for products purchased for ordinary home use in the* mainland states, Hawaii an Washington, **D.C. In Alaska** the **warrant** is the same **except** that it is **LIMITED** because you must pay to ship the production to the service shop or for the service technician's **travel** costs to your home.

All warranty service will be provided by our Factory Service Centers or by our authorized Customer Care servicers during **normal working hours.**

Should your appliance need service, during warranty period or beyond, call 800-GE-CARES (800-432-2737).

What is not covered

• Service trips to your home to teach you **how** to use the **product.**

Read your Owner's - A If you then have any questions about operating the **product,** please contact your **dealer** or our **Consumer Affairs** office at the address **below,** or **call, toll** free:

GE Answer Center" 800.626.2000 consumer information service

• Improper installation.

If you have an installation problem, contact your dealer or installer. You ar responsible for providing adequate electrical, exhausting and other connecting facilities.

- . **Replacement** of house **fuses** or resetting of circuit breakers.
- Failure of the product if it is misused, or used for other than **the** intended purpose or used commercially.
- . Damage to product caused by accident, **fire, floods** or acts of God.

WARRANTOR IS NOT RESPONSIBLE FOR CONSEQUENTIAL DAMAGES.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. To know what your legal rights are in your state, consult your local or state consumer affairs office or your state's Attorney General.

Warrantor: General Electric Company If further help is needed concerning this warranty, write: Manager-Consumer Affairs, GE Appliances, Louisville, KY 40225

Part No. 175D1807P085 Pub. No. 39-9332

Printed in Canada

NWXR473ET NWXR475. NKXR473ET NKXR473G1